

Bảng thông số sản phẩm

Thông số kỹ thuật



Vivace 10A 250V 1G Bell Press Switch with marking, Aluminium Silver

KB31BPB_AS

! Bán dịch vụ hạn chế

! Ngày sản xuất vào: 23 thg 1, 2021

! Ngày cung cấp dịch vụ vào: 24 thg 1, 2021

Main

Range	Vivace
Product Or Component Type	Bell press switch
Device Short Name	KB31
Device Application	Control switch
Additional Switch Application	Bell switch
Number Of Rocker	1
Switch Function	Press switch
Colour Tint	Aluminium silver

Complementary

Technology Type	Electromechanical
Device Presentation	Complete product
Marking	Bell symbol
Actuator	Push-button
Number Of Gangs	1 gang
Colour Tint	Aluminium silver
Material	Polycarbonate: grid plate Polycarbonate: surround Polycarbonate: base
Surface Finish	Matt
Surface Treatment	Painted
[Ue] Rated Operational Voltage	220...250 V
Type Of Packing	Plastic bag
Network Type	AC
Quantity Per Set	1
Sale Per Indivisible Quantity	1
Rated Current	10 A
Projecting Depth	8 mm
Device Mounting	Flush
Mounting Support	Wall mounted
Fixing Mode	By screw M3.5

Fixing Center	60.3 mm
Connections - Terminals	Screw terminal
Embedding Depth	25 mm
Number Of Terminals	2
Rated Current	10 A at 250 V AC, inductive 10 A at 250 V AC, resistive
[Ue] Rated Operational Voltage	250 V AC
Network Frequency	50/60 Hz
Contacts Material	Brass and phosphor bronze
Connections - Terminals	2 screw terminals
Terminal Identifier	L2 COM L1
Tightening Torque	0.4 N.m
Clamping Connection Capacity	<= 1.5 mm ² for rigid or stranded cable(s)
Wire Stripping Length	12 mm
Width	86 mm
Height	86 mm
Depth	37 mm

Environment

Standards	SS 227 MS IEC 60669-1 IEC 60669-1
Ambient Air Temperature For Operation	-5...40 °C
Relative Humidity	0...95 %
Operating Altitude	0...2000 m
Environmental Characteristic	Indoor use
Ip Degree Of Protection	IP20

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2.7 cm
Package 1 Width	8.6 cm
Package 1 Length	8.6 cm
Package 1 Weight	71 g
Unit Type Of Package 2	BB1
Number Of Units In Package 2	8
Package 2 Height	9.5 cm
Package 2 Width	15 cm
Package 2 Length	19 cm
Package 2 Weight	640 g

Unit Type Of Package 3	CAR
Number Of Units In Package 3	80
Package 3 Height	21 cm
Package 3 Width	31.5 cm
Package 3 Length	50 cm
Package 3 Weight	6010 g

Contractual warranty

Warranty	18 months
-----------------	-----------

Bền vững

Nhãn **Green Premium™** là cam kết của Schneider Electric trong việc cung cấp sản phẩm với hiệu suất môi trường tốt nhất. Green Premium cam kết tuân thủ các quy định mới nhất, minh bạch về tác động môi trường, cũng như các sản phẩm tuần hoàn và CO₂ thấp.

Hướng dẫn đánh giá tính bền vững của sản phẩm là tài liệu kỹ thuật phổ thông giúp làm rõ các tiêu chuẩn nhãn sinh thái toàn cầu và cách diễn giải việc khai báo môi trường.

[Tìm hiểu thêm về Green Premium >](#)

[Hướng dẫn đánh giá về sự bền vững của sản phẩm >](#)



RoHS/REACH

Hiệu suất sức khỏe

Mercury Free

Rohs Exemption Information [Yes](#)

Chứng nhận & Tiêu chuẩn

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Compliant with Exemptions

China Rohs Regulation

[China RoHS declaration](#)

Product out of China RoHS scope. Substance declaration for your information

Circularity Profile

No need of specific recycling operations