

Bảng thông số sản phẩm

Thông số kỹ thuật



Mureva Styl - 2-way control switch with LED surface mounting - grey

MUR35024

Main

Range Of Product	Mureva Styl
Device Presentation	Complete product
Technology Type	Electromechanical
Number Of Rocker	1
Colour Tint	Grey (RAL 7016)

Complementary

Device Mounting	Surface
Switch Function	1-pole 2-way
Actuator	Rocker
Rated Current	10 AX
Load Type	Load for energy saving lamps with ballast: 100 W
[Ue] Rated Operational Voltage	250 V AC
Local Signalling	LED (blue)
Led Current Consumption	0.15 mA at 250 V
Condition Of Use	Indoor/outdoor
Material	SEBS ABS (acrylonitrile butadiene-styrene) Brass
Fixing Mode	By screws
Clamping Connection Capacity	1.5...2.5 mm ² for rigid cable(s) 1.5...2.5 mm ² for stranded cable(s) 1.5...2.5 mm ² for flexible cable(s)
Wire Stripping Length	13 mm
Cable Entry	Easy valve access diameter: 6...20 mm
Chemical And Detergent Products Resistance	Resistant to alcohol (70 %) Resistant to alcohol (96 %) Resistant to A-Lactic Acid Resistant to diluted quaternary ammonium Resistant to diluted bleach Resistant to diluted ammonia Resistant to soapy water Resistant to crystal cleaner Resistant to hydrogen peroxide 10 volumes Resistant to hexane
Height	76 mm
Width	76 mm
Depth	64 mm

Projecting Depth	64 mm
------------------	-------

Environment

Quality Labels	AENOR EAC CE NF
----------------	--------------------------

Ip Degree Of Protection	IP55
-------------------------	------

Ik Degree Of Protection	IK08
-------------------------	------

Flame Retardance	Self-extinguishing 650 °C conforming to IEC 60695-2-1
------------------	-------------------------------------------------------

Standards	EN 60669-1
-----------	------------

Ambient Air Temperature For Operation	-5...40 °C
---------------------------------------	------------

Ambient Air Temperature For Storage	-25...55 °C
-------------------------------------	-------------

Packing Units

Unit Type Of Package 1	PCE
------------------------	-----

Number Of Units In Package 1	1
------------------------------	---

Package 1 Height	7.600 cm
------------------	----------

Package 1 Width	6.500 cm
-----------------	----------

Package 1 Length	7.600 cm
------------------	----------

Package 1 Weight	124.000 g
------------------	-----------

Unit Type Of Package 2	BB1
------------------------	-----

Number Of Units In Package 2	10
------------------------------	----

Package 2 Height	9.000 cm
------------------	----------

Package 2 Width	17.000 cm
-----------------	-----------

Package 2 Length	40.000 cm
------------------	-----------

Package 2 Weight	1.330 kg
------------------	----------

Unit Type Of Package 3	S04
------------------------	-----

Number Of Units In Package 3	60
------------------------------	----

Package 3 Height	30.000 cm
------------------	-----------

Package 3 Width	40.000 cm
-----------------	-----------

Package 3 Length	60.000 cm
------------------	-----------

Package 3 Weight	8.807 kg
------------------	----------

Bền vững

Nhãn **Green Premium™** là cam kết của Schneider Electric trong việc cung cấp sản phẩm với hiệu suất môi trường tốt nhất. Green Premium cam kết tuân thủ các quy định mới nhất, minh bạch về tác động môi trường, cũng như các sản phẩm tuần hoàn và CO₂ thấp.

Hướng dẫn đánh giá tính bền vững của sản phẩm là tài liệu kỹ thuật phổ thông giúp làm rõ các tiêu chuẩn nhân sinh thái toàn cầu và cách diễn giải việc khai báo môi trường.

[Tìm hiểu thêm về Green Premium >](#)

[Hướng dẫn đánh giá về sự bền vững của sản phẩm >](#)



Bao bì bền vững Minh bạch RoHS/REACH

Hiệu suất tài nguyên

Sustainable Packaging

Hiệu suất sức khỏe

Mercury Free

Rohs Exemption Information Yes

Chứng nhận & Tiêu chuẩn

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Compliant with Exemptions

China Rohs Regulation

[China RoHS declaration](#)

Product out of China RoHS scope. Substance declaration for your information

Environmental Disclosure

[Product Environmental Profile](#)

Circularity Profile

No need of specific recycling operations