


Bảng thông số sản phẩm

Thông số kỹ thuật



Socket-outlet, Avataron A, Universal, 16A, 250V, 3 Pin, 2S sized, White

M3T426UST_WE

Main

| | |
|----------------------------|------------------|
| Range Of Product | AvatarOn A |
| Product Or Component Typee | Socket-outlet |
| Device Presentation | Complete product |
| Colour Tint | White |
| Outlet Poles Configuration | 2P + E |
| Colour Tint | White |

Complementary

| | |
|------------------------------|-------------------------------------------------------------------------------------------------------------|
| Rated Current | 16 A at 250 V AC 50...60 Hz |
| Socket Number | 1 |
| Clamping Connection Capacity | 2 x 1.5...2 x 4 mm ² for solid cable(s) 2 x 1.5...2 x 4 mm ² for stranded cable(s) |
| Connections - Terminals | Screwless terminals |
| Material | Polycarbonate cover Polycarbonate base |
| Device Mounting | Flush |
| Width | 46.6 mm |
| Height | 69.3 mm |
| Depth | 36.35 mm |
| Embedding Depth | 24.85 mm |

Environment

| | |
|-----------------------------------------------|-------------|
| Ip Degree Of Protection | IP20 |
| Maximum Ambient Air Temperature For Operation | 35 °C |
| Ambient Air Temperature For Storage | -5...45 °C |
| Relative Humidity | 0...95 % |
| Operating Altitude | < 2000 m |
| Standards | IEC 60884-1 |
| Product Certifications | IEC |

Packing Units

| | |
|------------------------------|-----|
| Unit Type Of Package 1 | PCE |
| Number Of Units In Package 1 | 1 |

| | |
|------------------------------|----------|
| Package 1 Height | 3.6 cm |
| Package 1 Width | 4.7 cm |
| Package 1 Length | 7.0 cm |
| Package 1 Weight | 52.0 g |
| Unit Type Of Package 2 | BB1 |
| Number Of Units In Package 2 | 10 |
| Package 2 Height | 9.1 cm |
| Package 2 Width | 8.9 cm |
| Package 2 Length | 25.5 cm |
| Package 2 Weight | 852.0 g |
| Unit Type Of Package 3 | S03 |
| Number Of Units In Package 3 | 120 |
| Package 3 Height | 30.0 cm |
| Package 3 Width | 30.0 cm |
| Package 3 Length | 40.0 cm |
| Package 3 Weight | 7.463 kg |

Bền vững

Nhãn **Green Premium™** là cam kết của Schneider Electric trong việc cung cấp sản phẩm với hiệu suất môi trường tốt nhất. Green Premium cam kết tuân thủ các quy định mới nhất, minh bạch về tác động môi trường, cũng như các sản phẩm tuần hoàn và CO₂ thấp.

Hướng dẫn đánh giá tính bền vững của sản phẩm là tài liệu kỹ thuật phổ thông giúp làm rõ các tiêu chuẩn nhân sinh thái toàn cầu và cách diễn giải việc khai báo môi trường.

[Tìm hiểu thêm về Green Premium >](#)

[Hướng dẫn đánh giá về sự bền vững của sản phẩm >](#)



Minh bạch RoHS/REACH

Hiệu suất sức khỏe

Reach Free Of Svhc

Toxic Heavy Metal Free

Mercury Free

Rohs Exemption Information Yes

Chứng nhận & Tiêu chuẩn

Reach Regulation

[REACH Declaration](#)

Eu Rohs Directive

Compliant

[EU RoHS Declaration](#)

China Rohs Regulation

[China RoHS declaration](#)

Pro-active China RoHS declaration (out of China RoHS legal scope)

Environmental Disclosure

[Product Environmental Profile](#)

Circularity Profile

[End of Life Information](#)