

Product data sheet

Specifications



Switch Socket - 13A 250V - 3 phase 3 pole - flat pin - IP66 (grey)

S56C313GY

Main

Range	WPS
Product Or Component Type	Switch and socket-outlet
Colour Tint	Light grey
Motor M-Rating As3133	M80

Complementary

Control Type	Rotary
Material	PVC (polyvinyl chloride) UV stabilised
Surface Finish	Gloss
Width	101 mm
Height	203 mm
Rated Current	13 A
[Ue] Rated Operational Voltage	250 V
Network Frequency	50 Hz
Network Number Of Phases	3 phases
Number Of Gangs	2 gangs
Pin Number	3
Device Composition	Flat pin
Number Of Poles	3
Mounting Mode	Surface mounted

Environment

Ip Degree Of Protection	IP66
-------------------------	------

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	8.7 cm
Package 1 Width	10.3 cm
Package 1 Length	20.8 cm
Package 1 Weight	833.333 g
Unit Type Of Package 2	CAR

Number Of Units In Package 2	12
Package 2 Height	22 cm
Package 2 Width	30.3 cm
Package 2 Length	44 cm
Package 2 Weight	10000 g
Unit Type Of Package 3	P12
Number Of Units In Package 3	300
Package 3 Height	130 cm
Package 3 Width	80 cm
Package 3 Length	120 cm
Package 3 Weight	268000 g

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Eu Rohs Directive

Under investigation
