

# Bảng thông số sản phẩm

Thông số kỹ thuật



Socket, Mureva PK, panel-mounted, straight, 32A, 3P+N+E, 400V, IP67

PKF32G735

## Main

|                           |               |
|---------------------------|---------------|
| Range                     | Mureva        |
| Product Or Component Type | Socket        |
| Device Short Name         | Mureva socket |
| Plug, Socket Category     | Low voltage   |
| Poles Description         | 3P + N + E    |
| Network Type              | AC            |
| Outlet Standard           | Industrial    |

## Complementary

|                                     |   |
|-------------------------------------|---|
| Mounting Mode                       | Panel-mounted                                   |
| Plug, Socket, Control Station Shape | Straight  |
| [In] Rated Current                  | 32 A  |
| [Ue] Rated Operational Voltage      | 380...415 V                                     |
| Network Frequency                   | 50/60 Hz  |
| Ground Lug Clockwise Position       | 6 h   |
| Plug, Socket Material               | Housing: self-extinguishing engineering polymer |
| Contacts Material                   | Sleeves: brass                                  |
| Connections - Terminals             | Captive screws                                  |
| Cable Cross Section                 | 2.5...10 mm <sup>2</sup>                        |
| Net Weight                          | 0.297 kg  |
| Base Dimension                      | 90 x 100 mm                                     |
| Height                              | 100 mm  |
| Width                               | 102 mm  |
| Depth                               | 128 mm  |
| Colour                              | Grey (RAL 7035)                                 |
| Voltage Colour                      | Red   |

## Environment

|                         |                              |
|-------------------------|------------------------------|
| Standards               | IEC 60309-2<br>IEC 60309-1   |
| Ip Degree Of Protection | IP67 conforming to IEC 60529 |
| Ik Degree Of Protection | IK08 conforming to EN 62262  |

|  |   |
|--|---|
| <b>Fire Resistance</b>                       | 850 °C conforming to IEC 60695-2-1              |
| <b>Relative Humidity</b>                     | 50 % at 40 °C<br>70 % at 30 °C<br>90 % at 20 °C |
| <b>Ambient Air Temperature For Operation</b> | 35 °C ( 86400 s )                               |

## Packing Units

|                                     |          |
|-------------------------------------|----------|
| <b>Unit Type Of Package 1</b>       | PCE      |
| <b>Number Of Units In Package 1</b> | 1        |
| <b>Package 1 Height</b>             | 10.8 cm  |
| <b>Package 1 Width</b>              | 10 cm    |
| <b>Package 1 Length</b>             | 9 cm     |
| <b>Package 1 Weight</b>             | 276 g    |
| <b>Unit Type Of Package 2</b>       | BB1      |
| <b>Number Of Units In Package 2</b> | 6        |
| <b>Package 2 Height</b>             | 12 cm    |
| <b>Package 2 Width</b>              | 26.4 cm  |
| <b>Package 2 Length</b>             | 26.8 cm  |
| <b>Package 2 Weight</b>             | 1.797 kg |
| <b>Unit Type Of Package 3</b>       | S03      |
| <b>Number Of Units In Package 3</b> | 18       |
| <b>Package 3 Height</b>             | 30 cm    |
| <b>Package 3 Width</b>              | 30 cm    |
| <b>Package 3 Length</b>             | 40 cm    |
| <b>Package 3 Weight</b>             | 5.879 kg |

## Contractual warranty

|                 |           |
|-----------------|-----------|
| <b>Warranty</b> | 18 months |
|-----------------|-----------|

## Bền vững

Nhãn **Green Premium™** là cam kết của Schneider Electric trong việc cung cấp sản phẩm với hiệu suất môi trường tốt nhất. Green Premium cam kết tuân thủ các quy định mới nhất, minh bạch về tác động môi trường, cũng như các sản phẩm tuần hoàn và CO<sub>2</sub> thấp.

**Hướng dẫn đánh giá tính bền vững của sản phẩm** là tài liệu kỹ thuật phổ thông giúp làm rõ các tiêu chuẩn nhãn sinh thái toàn cầu và cách diễn giải việc khai báo môi trường.

[Tìm hiểu thêm về Green Premium >](#)

[Hướng dẫn đánh giá về sự bền vững của sản phẩm >](#)



Minh bạch **RoHS/REACH**

## Hiệu suất sức khỏe

Mercury Free

Rohs Exemption Information **Yes**

## Chứng nhận & Tiêu chuẩn

**Reach Regulation**

[REACH Declaration](#)

**Eu Rohs Directive**

Compliant with Exemptions

**China Rohs Regulation**

[China RoHS declaration](#)

Product out of China RoHS scope. Substance declaration for your information

**Environmental Disclosure**

[Product Environmental Profile](#)

**Circularity Profile**

No need of specific recycling operations