Product datasheet

Specifications



Auxiliary contact, GoPact MCCB 125/200/250, 1 NO/NC contact type, circuit breaker status OF/SD

G12-25AUX240

Main

main		
Range Of Product	GoPact MCCB	
Product Or Component Type	Auxiliary contact	
Device Short Name	OF and SD	
Device Application	Breaker status monitoring	
Range Compatibility	GoPact GoPact MCCB 125 GoPact GoPact MCCB 200 GoPact GoPact MCCB 250	
Signal Contacts Composition	1 NO/NC	

Complementary

Local Signalling	ON/OFF indication for open/close Trip indicator for voltage release indication Trip indicator for electrical fault
Mounting Mode	By screws
[Ith] Conventional Free Air Thermal Current	6 A
[Ue] Rated Operational Voltage	240 V AC
[le] Rated Operational Current	AC-12: 6 A at 12 V AC 50/60 Hz AC-12: 6 A at 24 V AC 50/60 Hz AC-12: 6 A at 24 V AC 50/60 Hz AC-12: 6 A at 110 V AC 50/60 Hz AC-12: 6 A at 240 V AC 50/60 Hz AC-14: 6 A at 12 V AC 50/60 Hz AC-14: 6 A at 24 V AC 50/60 Hz AC-14: 6 A at 48 V AC 50/60 Hz AC-14: 6 A at 110 V AC 50/60 Hz AC-14: 6 A at 110 V AC 50/60 Hz DC-12: 6 A at 12 V DC DC-12: 6 A at 12 V DC DC-12: 1 A at 48 V DC DC-12: 0.5 A at 110 V DC DC-12: 0.25 A at 220 V DC
Mechanical Durability	10000 cycles
Auxiliary Connection Terminal	Pre-wired 0.5 mm ²
Cable Length	500 mm

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	6.5 cm
Package 1 Width	8.5 cm

Price is "List Price" and may be subject to a trade discount - check with your local distributor or retailer for actual price.

Package 1 Length	4.8 cm
Package 1 Weight	600 g
Unit Type Of Package 2	S03
Number Of Units In Package 2	60
Package 2 Height	30 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	4.041 kg
Unit Type Of Package 3	P06
Number Of Units In Package 3	720
Package 3 Height	60 cm
Package 3 Width	60 cm
Package 3 Length	80 cm
Package 3 Weight	56.992 kg

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

Well-being performance

	Reach Free Of Svhc	
	Mercury Free	
	Rohs Exemption Information	Yes
	Pvc Free	
Rea	ch Regulation	REACh Declaration
Eu F	cohs Directive	Compliant
		EU RoHS Declaration
Chin	a Rohs Regulation	China RoHS declaration
Wee	e	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins