

# Bảng thông số sản phẩm

Thông số kỹ thuật



Enclosure, Resi9 MP, surface mounting, 1 row of 4 modules, IP40, translucent door, 1 earth + 1 neutral terminal blocks

MIP12104T

## Main

Range	Resi9
Product Name	Resi9 MP
Product Or Component Type	Enclosure
Enclosure Type	Modular enclosure
Nb Of 18 Mm Modules Per Row	4
Nb Of Horizontal Rows	1
Type Of Door	Translucid
Width	124 mm outside:
Height	198 mm outside:
Depth	95 mm outside:

## Complementary

Enclosure Mounting	Surface
9 Mm Pitches	8
Total Number Of 18 Mm Modules	4
[In] Rated Current	50 A
Type Of Rail	35 mm asymmetrical rail
Mounting Plate Description	Without mounting plate
Cable Entry	1 trunking flange 1 bare flange
Terminal Block Function	Earth / neutral
Number Of Terminal Blocks	1 earth (screwed) with 4 outgoing 1 neutral (screwed) with 4 outgoing
Distribution Block Outgoers	1 x 16 mm <sup>2</sup> for earth 1 x 16 mm <sup>2</sup> for neutral 1 x 6 mm <sup>2</sup> for earth 1 x 6 mm <sup>2</sup> for neutral 2 x 10 mm <sup>2</sup> for earth 2 x 10 mm <sup>2</sup> for neutral
Enclosure Material	Back part: technoplastic Door: technoplastic Front face: technoplastic
Internal Depth	74 mm
Colour	Front face: white (RAL 9003) Door: translucid
Market Segment	Small commercial Residential

## Environment

<b>Standards</b>	IEC 61439-1 IEC 61439-3 IEC 60670-1 IEC 60670-24
<b>Quality Labels</b>	IMQ
<b>Fire Resistance</b>	Door: 650 °C Back part: 650 °C Front face: 650 °C
<b>Ip Degree Of Protection</b>	IP40
<b>Ik Degree Of Protection</b>	IK07
<b>Ambient Air Temperature For Operation</b>	-25...60 °C

## Packing Units

<b>Unit Type Of Package 1</b>	PCE
<b>Number Of Units In Package 1</b>	1
<b>Package 1 Height</b>	9.550 cm
<b>Package 1 Width</b>	12.400 cm
<b>Package 1 Length</b>	19.800 cm
<b>Package 1 Weight</b>	400.000 g
<b>Unit Type Of Package 2</b>	BB1
<b>Number Of Units In Package 2</b>	20
<b>Package 2 Height</b>	52.000 cm
<b>Package 2 Width</b>	30.000 cm
<b>Package 2 Length</b>	40.000 cm
<b>Package 2 Weight</b>	8.100 kg
<b>Unit Type Of Package 3</b>	P12
<b>Number Of Units In Package 3</b>	320
<b>Package 3 Height</b>	120.000 cm
<b>Package 3 Width</b>	80.000 cm
<b>Package 3 Length</b>	120.000 cm
<b>Package 3 Weight</b>	141.600 kg

## Contractual warranty

<b>Warranty</b>	18 months
-----------------	-----------

## Bền vững

Nhãn **Green Premium™** là cam kết của Schneider Electric trong việc cung cấp sản phẩm với hiệu suất môi trường tốt nhất. Green Premium cam kết tuân thủ các quy định mới nhất, minh bạch về tác động môi trường, cũng như các sản phẩm tuần hoàn và CO<sub>2</sub> thấp.

**Hướng dẫn đánh giá tính bền vững của sản phẩm** là tài liệu kỹ thuật phổ thông giúp làm rõ các tiêu chuẩn nhãn sinh thái toàn cầu và cách diễn giải việc khai báo môi trường.

[Tìm hiểu thêm về Green Premium >](#)

[Hướng dẫn đánh giá về sự bền vững của sản phẩm >](#)



Minh bạch **RoHS/REACH**

## Hiệu suất sức khỏe

Mercury Free

Rohs Exemption Information **Yes**

Halogen Free Product

## Chứng nhận & Tiêu chuẩn

**Reach Regulation**

[REACH Declaration](#)

**Eu Rohs Directive**

Pro-active compliance (Product out of EU RoHS legal scope)

**China Rohs Regulation**

[China RoHS declaration](#)

Product out of China RoHS scope. Substance declaration for your information

**Environmental Disclosure**

[Product Environmental Profile](#)

**Circularity Profile**

No need of specific recycling operations